

# NVC-HD4616GIF30 NVC-HD4616GIM30 NVC-HD4616GIA30

## HD Network IR Bullet Camera



### FEATURE

- ☑ H.265/H.264/MPEG, Support Multiple Code Stream
- ☑ HDTV, 3MP Full RealTime Transmission
- ☑ Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- ☑ Support 3D DNR, Mobile Surveillance, IR 30M&42pcs IR LED, Weatherproof IP66
- ☑ Support WDR, Support DC12V/POE (DC12V/AC24V Optional)



### SPECIFICATION

Model	Model No.	NVC-HD4616GIF30	NVC-HD4616GIM30	NVC-HD4616GIA30	
Camera	Type	3 Megapixel HD Network IR Bullet Camera			
	Sensor	1/3" Progress Scan CMOS			
	Resolution	Main Stream	2592*1520, 1-15FPS; 2048*1520, 1-25(30)FPS; 1920*1080, 1-25(30)FPS		
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS		
	Min. Illumination	Color 0.1Lux@F1.2; B/W 0Lux@F1.2 (IR ON)			
	IR Distance	IR 30M&42pcs IR LED			
	S/N Ratio	≥52db			
	WDR	≥120db			
	Electronic Shutter	1~1/10000 sec, Automatic			
	Lens	6mm(3.6/8/12mm Optional) Fixed Lens	2.8-12mm Manual Zoom Lens	2.8-12mm 3MP Motorized Focus Lens	
Day & Night	IR Cut Optical Filter				
Audio/Video Setting	Video Compression	H.265/H.264/ M-JPEG, Support Multiple Code Stream			
	Code Stream	32Kbps-16Mbps, Support CBR/VBR			
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA			
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control			
	Image Flip	Horizontal, Vertical, Horizontal&Vertical			
	Motion Detection	Support			
	Privacy Mask	Support			
	3D DNR	High/Medium/Low			
	OSD Setting	Support Channel Name, Date Time, Code Stream Overlay			
	Interface	10/100 M Ethernet (RJ-45)			
Network	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP			
	ONVIF	Support			
	Access Control	Administer and Common User			
	Web Browser	IE 6.0 and Above			
	Max. User Number	≤10			
General	CVBS	Optional			
	Audio I/O	Support			
	Alarm I/O	Optional			
	Mobile Surveillance	Support			
	Working Conditions	-10°C ~ 50°C; 10% to 90%, (Non-Condensing)			
	Power Supply	DC12V/POE (DC12V/AC24V Optional)			
	Dimension(mm)	315(L) x90(W)x100(H)mm			
Weight(with package)	840g				

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

### Dimension (Unit : mm)

