

NVD-HD5310PF


NVD-HD5310PIF



HD Network (IR) Vandal-proof Dome Camera

FEATURE

- ☑ HDTV, 720P/1024P Full RealTime Transmission
- ☑ Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- ☑ Support 3D DNR, Mobile Surveillance Vandal-proof IK10, Weatherproof IP66, (IR 20M Optional)
- ☑ Support DWDR, Support DC12V/POE (DC12V/AC24V Optional)
- ☑ Anti Reflection, Scratch-proof



SPECIFICATION

Model	Model No.		HD5310PF	NVC-HD5310PIF
	Type		1.3MP HD Network Vandal-proof Dome Camera	1.3MP HD Network IR Vandal-proof Dome Camera
Camera	Sensor		1/1.8" Progress Scan CMOS	
	Resolution	Main Stream	1280*1024, 1-25(30)FPS; 1280*960, 1-25(30)FPS; 1280*720, 1-25(30)FPS	
		Sub Stream	720*576, 1-25(30)FPS; 640*480, 1-25(30)FPS	
	Min. Illumination		Color 0.1Lux@F1.2; B/W 0.01Lux@F1.2	
	IR Distance		/	20M
	S/N Ratio		≥52db	
	WDR		≥80db	
	Electronic Shutter		1~ 1/10000 sec.	
	Lens		3.6mm (2.8/6/8/12mm Optional) Fixed Lens	3.6mm Fixed Lens/ 12pcs IR LED
	Day & Night		IR Cut Optical Filter	
Audio& Video Setting	Video Compression		H.264(Baseline, Main Profile)/ M-JPEG, Support Multiple Code Stream	
	Code Stream		32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment		Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA	
	Intelligent Features		Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control	
	Image Flip		Horizontal, Vertical, Horizontal& Vertical	
	Motion Detection		Support	
	Privacy Mask		Support	
	3D DNR		High/Medium/Low	
	OSD Setting		Support Channel Name, Date Time, Code Stream Overlay	
	Interface		10/100 M Ethernet (RJ-45)	
Network	Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPoE, SMTP, UPNP	
	ONVIF		Support	
	Access Control		Administer and Common User	
	Web Browser		IE 6.0 and Above	
	Max. User Number		≤10	
General	CVBS		/	
	Audio I/O		Support	
	Alarm I/O		/	
	Mobile Surveillance		Support	
	Working Conditions		-10°C ~ 50°C; 10% to 90% (Non-Condensing)	
	Power Supply		DC12V/POE (DC12V/AC24V Optional)	
	Dimension(mm)		125(Φ)x70(H)mm	
	Weight(with package)		390g	

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

Dimension (Unit : mm)

