

# NVC-HD4599GIM50 NVC-HD4599GIA50

## HD Network Starlight 50M IR Bullet Camera



### FEATURE

- ☑ Starlight Low Illumination
- ☑ H.265/H.264/MJPEG, Support Multiple Code Stream
- ☑ HDTV, 720P/1024P/1080P Full RealTime Transmission
- ☑ Support ONVIF, Built-in Auto Double Filter Switching Mechanism, True Day/Night
- ☑ Support 3D DNR, Mobile Surveillance, IR 50M, Weatherproof IP66
- ☑ Support WDR, Support DC12V/POE (DC12V/AC24V Optional)



### Specification:

Model	Model No.	NVC-HD4599GIM50	NVC-HD4599GIA50	
	Type	2 Megapixel HD Network Starlight 50M IR Bullet Camera		
Camera	Sensor	1/2.8" Progress Scan CMOS		
	Resolution	Main Stream	1920*1080, 1-25(30)FPS; 1280*720, 1-25(30)FPS	
		Sub Stream	704*576, 1-25(30)FPS; 640*480, 1-25(30)FPS	
	Min. Illumination	Color: 0.001Lux@F1.2; B/W 0Lux@F1.2 (IR ON)		
	IR Distance	50M		
	S/N Ratio	≥52db		
	WDR	≥120db		
	Electronic Shutter	1~1/10000 sec, Automatic		
	Lens	2.8-12mm Manual Zoom Lens	2.8-12mm 3MP Motorized Focus Lens	
	Day & Night	IR Cut Optical Filter		
Audio/Video Setting	Video Compression	H.265/H.264/ M-JPEG, Support Multiple Code Stream		
	Code Stream	32Kbps-16Mbps, Support CBR/VBR		
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA		
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control		
	Image Flip	Horizontal, Vertical, Horizontal& Vertical		
	Motion Detection	Support		
	Privacy Mask	Support		
	3D DNR	High/Medium/Low		
	OSD Setting	Support Channel Name, Date Time, Code Stream Overlay		
	Network	Interface	10/100 M Ethernet (RJ-45)	
Protocol		TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP		
ONVIF		Support		
Access Control		Administer and Common User		
Web Browser		IE 6.0 and Above		
General	Max. User Number	≤10		
	CVBS	Optional		
	Audio I/O	Support		
	Alarm I/O	Optional		
	Mobile Surveillance	Support		
	Working Conditions	-10°C ~ 50°C; 10% to 90%, (Non-Condensing)		
	Power Supply	DC12V/POE (DC12V/AC24V Optional)		
	Dimension(mm)	345(L) x100(W)x100(H)mm		
Weight(with package)	980g			

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor /Outdoor Places.

### Dimension (Unit : mm)

