


NVD-HD5516PA NVD-HD5516PIA

HD Network (IR) Vandal-proof Metal Dome Camera



FEATURE

- ☑ HDTV, 720P/ 1024P/1080P Full Real Time Transmission, True Day/Night
- ☑ Support ONVIF, Built-in Auto Double Filter Switching Mechanism
- ☑ Support 3D DNR, Mobile Surveillance/Vandal-proof IK10
- ☑ Support WDR, Support DC12V/AC24V/POE
- ☑ Weatherproof IP66, IR 30M Optional, Anti-reflection, Scratch-proof



SPECIFICATION

Model	Model No.	NVD-HD5516PA	NVD-HD5516PIA
	Type	2 Megapixel HD Network Vandal-proof Metal Dome Camera	2 Megapixel HD Network IR Vandal-proof Metal Dome Camera
Camera	Sensor	1/2.8" Progress Scan CMOS	
	Resolution	Main Stream	1920*1080, 1-25(30)FPS; 1280*720, 1-25(30)FPS
		Sub Stream	704*576, 1-25(30)FPS, 640*480, 1-25(30)FPS
	Min. Illumination	Color 0.1Lux@F1.2; B/W 0.01LUX (IR On)	Color 0.1Lux@F1.2; B/W 0 LUX (IR On)
	IR Distance	/	30M
	S/N Ratio	≥52db	
	WDR	≥120db	
	Electronic Shutter	1~ 1/10000 sec. Auto	
	Lens	2.8-12mm Motorized Focus Lens	2.8-12mm Motorized Focus Lens/ 24pcs IR LED
	Day & Night	IR Cut Optical Filter	
Audio/Video Setting	Video Compression	H.264 (Baseline, Main Profile)/M-JPEG, Support Multiple Code Stream	
	Code Stream	32Kbps-16Mbps, Support CBR/VBR	
	Video Adjustment	Brightness/ Contrast / Chroma/ Saturation/ Sharpness / GAMMA	
	Intelligent Features	Intelligent Code Stream, Video Mask, Out-of-focus Detection, Intelligent Switch Control	
	Image Flip	Horizontal, Vertical, Horizontal& Vertical	
	Motion Detection	Support	
	Privacy Mask	Support	
	3D DNR	High/ Medium/ Low	
	OSD Setting	Support Channel Name, Date Time, Code Stream Overlay	
	Interface	10/100 M Ethernet (RJ-45)	
Network	Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
	ONVIF	Support	
	Access Control	Administer and Common User	
	Web Browser	IE 6.0 and Above	
	Max. User Number	≤10	
	CVBS	Optional	
	Audio I/O	Support	
	Alarm I/O	Optional	
	SD Card	Support	
	Mobile Surveillance	Support	
Working Conditions	-10°C ~ 50°C; 10% to 90%, (Non-Condensing)		
Power Supply	DC12V/AC24V/POE		
Dimension(mm)	150(Φ)x100(H)mm		
Weight(with package)	780g		

For Financial, Prison, Supermarket, Telecom, Government, School, Airport, Factory, Hotel and Other Indoor/ Outdoor Places.

Dimension (Unit : mm)

